

ResinDek® LD Product Description

ResinDek LD floor panels are a tremendous value for warehouses, distribution centers and multi-level self-storage facilities. ResinDek LD economical wood flooring panel is manufactured with mostly recycled and recovered wood fibers, environmentally friendly resins with no added urea formaldehyde, and a wax emulsifier for moisture resistance. The ingredients are combined and compressed under extremely high pressure and temperature, resulting in a panel with superior physical properties.

ResinDek composite engineered flooring panels are custom manufactured and available in sizes up to 4' x 10' (1206 mm x 3048 mm). Each panel features a tongue-and-groove configuration that effectively promotes panel to panel wheel load transfer. When required, tongue-and-groove configurations are available on all 4 sides or with square edges.

SCS Global Certifications, LEED® and FSC®

ResinDek LD panels are certified to have No Added Formaldehyde and conforms to SCS Recycled Content Standard V7-0. ResinDek panels can contribute towards earning points for LEED® qualified buildings. When required ResinDek panels are available with FSC® Certification. FSC® License Code FSC-C124474.

Flame Spread Index

When tested in accordance with ASTM E84, the ResinDek panels plus the corrugated metal deck assembly meet Class A criteria for an interior finish.

Uniform Evaluation Service Report

ResinDek floor panels have been independently evaluated and approved for use in Types I-V construction and as part of a fire-resistance rated assembly by the IAPMO Uniform Evaluation Services. United States ER Number 467. Canada ER Number UEL 5027.

UL Classification

ResinDek® flooring system can be UL Classified for up to a 2 hour fire rated assembly under UL Design No. L701 and UL File No. R39265.

ResinDek® LD Specifications

Manufactured by Cornerstone Specialty Wood Products, LLC®, ResinDek LD shall be .75" thick and have the durability and structural integrity to support rolling pallet jack rolling loads up to 2,000 lbs with 20 GA B-Deck and AMR loads up to 500 lbs with 20 GA B-Deck. The panel shall feature a tongue and groove configuration along the two long edges. The recommended finish shall be determined based upon the type and volume of traffic traveling on the floor. **For detailed ResinDek LD Master Specifications please email or call Cornerstone Specialty Wood Products.**

ResinDek® LD Quick Specs

Panel Thickness: 3/4"

Panel Weight: 2.8 psf or 4.2 psf with MetaGard® finish

Pallet Jack & Product Load Limits

- Pallet jack rolling loads up to 2,000 lbs with 20 GA B-Deck

Mobile Robot & Product Load Limits

- AMR rolling loads up to 500 lbs with 20 GA B-Deck
- Robot contact pressure is 500 psi

Available Finishes

For Heavy Equipment, Storage, Rolling Carts & Pallet Jacks

- Gray Diamond Seal® Coating
- Gray Diamond Seal® ESD Coating
- MetaGard® GVT Steel Decking Surface
- Unfinished (UF)

For AGV & AMR Robotic Traffic

- TriGard® ESD Coating
- TriGard® ESD Ultra Coating
- MetaGard® SST Steel Decking Surface

ResinDek® Options

- Invisi-Loc® Underside Fasteners
- Collated Screws
- Custom Tongue & Groove Configurations
- Available in sizes up to 4' x 10' (ResinDek with MetaGard max size is 4'x 8')

Our Services

- CAD drawings that optimize materials
- Pre-job planning and on-site consultations
- Installation support for training
- Logistics support to coordinate deliveries
- Cut to size panels
- Custom testing for specific applications

10-Year Product Warranty

Cornerstone Specialty Wood Products, LLC® (CSWP) hereby warrants ResinDek LD panels to be free from defect, structurally sound, and able to safely carry the specified design loads. The warranty will flow through and transfer to the end user for the entire period of the warranty.